

**In The Claims:**

---

1. (Currently Amended) A communications system comprising:  
stratospheric platform having a payload controller and a phased array  
antenna having a plurality of elements; and

a gateway station in communication with said stratospheric platform, said  
gateway station scaling the plurality of elements to form a reconfigurable plurality of  
beams, said gateway station communicating a control signal to the stratospheric platform  
to communicate a scaling of elements having adaptive interference rejection.

2. (Original) A communications system as recited in claim 1,  
wherein the payload controller comprises a demultiplexer for receiving control signals.

3. (Original) A communications system as recited in claim 2,  
wherein the demultiplexer generates a plurality of element control signals.

4. (Original) A system as recited in claim 3, wherein the element  
control signals are coupled to an RF feed, the RF feed is coupled to elements of said  
phased array antenna.

5. (Original) A system as recited in claim 1, wherein the gateway  
station comprises a beam generator for generating beam signals.

6. (Original) A system as recited in claim 1, wherein the gateway  
station comprises a digital beam former circuit having a digital beam former, an adaptive  
beam processor coupled to user position files, said digital beam former circuit coupled to  
the beam generator, the digital beam former generates a plurality of element control  
signals, said adaptive beam processor generating said adaptive interference rejection.

7. (Original) A system as recited in claim 1, wherein said gateway station further comprises a multiplexer/demultiplexer.

8. (Original) A system as recited in claim 7, wherein said multiplexer/demultiplexer comprises a code division multiplexer/demultiplexer.

9. (Original) A system as recited in claim 1, wherein said ground station is coupled to a terrestrial network.

91 10. (Original) A system as recited in claim 9, wherein said terrestrial network comprises the Internet.

11. (Original) A system as recited in claim 9, wherein the terrestrial network comprises the public service telephone network.

12. (Original) A communications system, comprising:  
a ground station having;  
a beam generator for generating a plurality of beam control signals,  
a digital beam former circuit receiving the beam control signals and generating a plurality of first element control signals having adaptive interference rejection in response to the beam control signals,  
a multiplexer multiplexing the first element control signals, and  
an RF subsystem for communicating an RF signal corresponding to the first element control signals;  
a stratospheric platform having;  
a payload receiver for receiving the RF signals,  
a demultiplexer demultiplexing the RF signals into a second plurality of element control signals corresponding to the first element control signals and generating a plurality of beams in response to the second plurality of element control signals.

13. (Original) A system as recited in claim 12, wherein said ground station comprises a gateway station.

14. (Original) A system as recited in claim 12, wherein said ground station is coupled to a terrestrial network.

15. (Original) A system as recited in claim 14, wherein said terrestrial network comprises the internet.

91 16. (Original) A system as recited in claim 15, wherein the terrestrial network comprises the public service telephone network.

17. (Original) A system as recited in claim 12, wherein a digital beam former circuit having a digital beam former, an adaptive beam processor coupled to user position files, said digital beam former circuit coupled to the beam generator, the digital beam former generates a plurality of element control signals, said adaptive beam processor generating said adaptive interference rejection.

18. (Currently Amended) A method of controlling a communications system having a stratospheric platform with a phased array antenna with a plurality of elements, said method comprising the steps of:

forming a plurality of beams in a gateway station by scaling a plurality of elements using adaptive interference rejection;

communicating the scaling of elements to a stratospheric platform; and

generating the beams in response to the scaling of elements by the stratospheric platform.

19. (Original) A method as recited in claim 18 wherein said step of forming comprises the step of estimating interference on a first beam from a second beam.

20. (Original) A method as recited in claim 19 wherein said step of forming comprises the step of estimating interference values from user position values and creating said adaptive interference rejection by subtracting interference values from the plurality of beams.

---